




NDS[®]
We put water in its place


NDS, INC.
851 NORTH HARVARD AVE.
LINDSAY, CA 93247
TOLL FREE: 1-800-726-1994
PHONE: (559) 562-9888
FAX: (559) 562-4488
www.ndspro.com



Type of Traffic	Concrete Encasement - Width each side "A" & Depth Below Channel "B"	Width of Channel	Depth of Channel	Depth of Slot Top + 1/8" Recess	Width of Excavation*	Depth of Excavation*
Pedestrian/ Class A	4"	6"	4" to 12"	5.3"	14"	13.3" to 21.3"
Light Duty/ Class B	4"	6"	4" to 12"	5.3"	14"	13.3" to 21.3"
Medium Duty/ Class C	6"	6"	4" to 12"	5.3"	18"	15.3" to 23.3"
Heavy Duty/ Class D	8"	6"	4" to 12"	5.3"	22"	17.3" to 25.3"

NOTES:

1. CHANNELS TO BE INSTALLED WITH SLOT TOP. PROTECT FROM CONCRETE POUR BY COVERING WITH TAPE.
2. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
3. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 558-011.



DURA SLOPE TRENCH DRAIN SYSTEM-SLOT TOP
REBAR SUSPENSION METHOD

