

### ADA HEELPROOF COMBee grating



#### Product Features:

- Certified to EN 1433 Load Class C 250 kN 56,200 lbs.
- Uses fiX self-locking system.
- Suitable to use with NW100 channels.
- Manufactured from composite plastic.
- With antislip surface structure.
- Complies with ADA - American Disabilities Act.

#### Installation:

- The trench drain system and grates shall be installed in accordance with the manufacturer's installation instructions and recommendations.

#### Gratings FILCOTEN® pro – v 100 (4") with fiX self-locking system.

	Item no.	Gratings	Material	Dimension	Load class as per EN-standard	Slot-/Mesh width	Weight		Inlet cross-section sq.inches	Inlet cross-section cm2/m
							Lbs	Kg		
○	17010402	ADA HEELPROOF COMBee grating	Polyamide	19.40"/4.84"/0.78" 500/123/20	C 250 kN	Ø 0.29" hole (7.3 mm)	2.43	1.1	44.95	290

**Specification:** FILCOTEN pro-tec NW100, heavy duty, (Load Class C 250 kN), composite plastic, reinforced grate is 4.84" (123mm) wide, 19.70" (500mm) long, 0.78" (20mm) high, weighing 2.43 lbs (1.1 kg). The grate has Ø 0.29" (7.3mm) diameter hole and is ADA compliant and Class C load rated - commercial applications. The grate is secured to the body with four point fiX self-locking (snap-on) system. Composite plastic manufactured and tested according to EN1433 - CE certified.

C250kN Ø7,3: PA 17010402

