

NDS, INC. 851 N. HARVARD AVE. LINDSAY, CA 93247 TOLL FREE: 1-800-726-1994 PHONE: (559) 562-9888 FAX: (559) 562-4488

www.ndspro.com

> PLAN VIEW (C250kN SW12,5: V 17110281)

SIDE VIEW (C250kN SW12,5: V 17110281)

ITEM#	GRATINGS	MATERIAL	DIMENSION	LOAD CLASS AS PER	SLOT-/MESH	WEIGHT		INLET CROSS	INLET CROSS
				EN-STANDARD	WIDTH	LBS	KG	SECTION	SECTION
17110281	MAINTENANCE	GALVANIZED	19.70"/4.84"/5.24"	C 250 KN	SW 0.49"	11.02	5.0	19.37 SQ.IN/M	125 CM ² /M
	UNIT SH 110MM	STEEL	500/123/133		(SW 12.5MM)				
13399	LIFTING KNOBS	STEEL AND	ACCESSORIES			0.22	0.1	N/A	N/A
		PLASTIC	(2 PIECES OF LIFTING KNOBS FOR MAINTENANCE UNIT)						

PRODUCT FEATURES:

- CERTIFIED TO EN 1433 LOAD CLASS C 250 KN 56,200 LBS.
- SUITABLE TO USE WITH NW100 CHANNELS.
- MANUFACTURED FROM GALVANIZED STEEL.
- COMPLIES WITH ADA AMERICAN DISABILITIES ACT.

INSTALLATION:

- THE TRENCH DRAIN SYSTEM AND SLOT TOPS SHALL BE INSTALLED IN ACCORDANCE WITH THE MANUFACTURER'S INSTALLATION INSTRUCTIONS AND RECOMMENDATIONS.

SLOT TOPS ASYMETRIC FILCOTEN® LIGHT/TEC/PRO 100 (4") - MAINTENANCE UNIT SPECIFICATION:

FILCOTEN PAVE SLOT TOP FOR NW100 TRENCH DRAINS, HEAVY DUTY, (LOAD CLASS C 250 KN), GALVANIZED STEEL. THE REINFORCED SLOT TOP IS 4.84" (123MM) WIDE, 19.70" (500MM) LONG, 5.24" (133MM) HIGH, 11.02 LBS (5.0 KG) WEIGHT. FILCOTEN PAVE MAINTENANCE UNIT HAS THE SLOT 0.49" (12.5MM) WIDE, AND IS ADA COMPLIANT AND CLASS C - FOR COMMERCIAL APPLICATIONS. FILCOTEN PAVE SLOT TOP AND MAINTENANCE UNITS ARE SUITABLE TO USE WITH NOMINAL WIDTH 4" (100MM) TRENCH DRAINS. RECOMMENDED MINIMUM 2 MAINTENANCE UNITS FOR A RUN, AND 2 PIECES OF LIFTING KNOBS. GALVANIZED STEEL MANUFACTURED AND TESTED ACCORDING TO EN1433 - CE CERTIFIED.

NOTES:

- 1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
- 2. DO NOT SCALE DRAWING.
- 3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY.
- 4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.



www.ndspro.com/s5